according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023 Print date: 29 Mar 2023

Version: 4



optiprint lumina (all colors)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier

Trade name/designation:

optiprint lumina (all colors)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

3 D printing resin for the additivemanufacturing of temporary crowns and bridges Only to be used in the 3 D printer and by trained personnel

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor): dentona AG

Otto-Hahn-Str. 27 44227 Dortmund Germany Telephone: 0231-5556-0 Telefax: 0231-5556-30 E-mail: info@dentona.de Website: www.dentona.com

1.4. Emergency telephone number

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	Calculation method.
Serious eye damage/eye irritation (Eye Dam. 1)	H318: Causes serious eye damage.	Calculation method.
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	Calculation method.
Hazardous to the aquatic environment (Aquatic Acute 1)	H400: Very toxic to aquatic life.	Calculation method.
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	Calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



according to Regulation (EC) No. 1907/2006 (REACH) **Revision date:** 21 Mar 2023

Print date: 29 Mar 2023 Version: 4



optiprint lumina (all colors)

Signal word: Danger

Hazard statements for health hazards		
H317 May cause an allergic skin reaction.		
H318	Causes serious eye damage.	
H332	H332 Harmful if inhaled.	
Hazard sta	Hazard statements for environmental hazards	

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Supplemental hazard information: none

Precautionary statements Prevention		
P261	261 Avoid breathing dust/fume/gas/mist/vapours/spray.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P273	Avoid release to the environment.	
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/		

Precautionary statements Response

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Special rules for supplemental label elements for certain mixtures:

- 29,8 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (oral).
- 19,7 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (dermal).
- 68,6 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (inhalative).
- 19,7 % percent of the mixture consists of components of unknown hazards to the aquatic environment.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

lazaraous ingreatenes	ardous ingredients / nazardous impurities / Stabilisers:		
Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration	
CAS No.: 72869-86-4 EC No.: 276-957-5 REACH No.: 01-2120751202-68-XXXX	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12- diazahexadecane-1,16-diylbismethacrylate Aquatic Chronic 2 (H411), Skin Sens. 1B (H317) Warning	22 - < 45 weight-%	
CAS No.: 14464-46-1 EC No.: 238-455-4	Christobiltmehl The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	12 - < 25 weight-%	
CAS No.: 109-16-0 EC No.: 203-652-6	Triethylene glycol Dimethacrylate Aquatic Chronic 3 (H412), Skin Sens. 1 (H317) Warning	5 - ≤ 9.7 weight-%	
CAS No.: 1245638-61-2 EC No.: 629-850-6	2-Propenoic acid Acute Tox. 4 (H302), Aquatic Chronic 2 (H411), Eye Dam. 1 (H318), Skin Irrit. 2 (H315), Skin Sens. 1 (H317)	4 - < 7.15 weight-%	
CAS No.: 75980-60-8 EC No.: 278-355-8 Index No.: 015-203-00-X REACH No.: 01-2119972295-29-0000	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 2 (H361f) Warning	0 - ≤ 1.54 weight-%	

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 21 Mar 2023 Print date: 29 Mar 2023 Version: 4



optiprint lumina (all colors)

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 108-88-3 EC No.: 203-625-9 Index No.: 601-021-00-3 REACH No.: 01-2119957862-25-XXXX	toluene Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), Repr. 2 (H361d***), STOT RE 2 (H373**), STOT SE 3 (H336), Skin Irrit. 2 (H315)	0 - < 0.01 weight-%

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

When in doubt or if symptoms are observed, get medical advice. I In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended. Warning First aider: Pay attention to self-protection!

Following inhalation:

In case of irritation of the respiratory tract by the product: Consult a doctor Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/attention.

In case of skin contact:

Wash off with plenty of soap and water and rinse. After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

In case of contact with eyes, remove contact lenses and immediately rinse with running water for 10 to 15 minutes with the eyelids open and consult an ophthalmologist. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:

Rinse mouth. Let 1 glass of water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person or a person with cramps. Avoid vomiting

Self-protection of the first aider:

Remove contaminated, saturated clothing.Use personal protection equipment. No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: May cause allergic skin reactions. Allergic reactions: Severe eye irritation/irritation Allergic reactions Serious eye damage/eye irritation

4.3. Indication of any immediate medical attention and special treatment needed Note to doctor: Treat symptomatically. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray, foam, dry extinguisher or carbon dioxide. Water spray jet alcohol resistant foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media:

Do not use water jet as extinguishing agent as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition or combustion products may contain the following substances: Carbon oxides. Combustible

Hazardous combustion products:

In case of fire: Gases/vapours, toxic

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023

Print date: 29 Mar 2023 Version: 4

dentona[®]

optiprint lumina (all colors)

5.3. Advice for firefighters

Protective measures during firefighting: No actions should be taken without appropriate training or that involve personal risk.Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Special protective equipment for fire fighters: Wear positive pressure breathing apparatus (SCBA) and suitable protective clothing. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear suitable protective clothing, including gloves, goggles / face shield, respirator, boots, clothing or apron, as appropriate, when working. Wear suitable respiratory protection if ventilation is inadequate. Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Environmental precautions Avoid release to the environment. Do not allow to enter drains or water courses. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Do not smoke, no sparks, flames or other sources of ignition near spills. Bind spilled material with sand or other inert absorbent. Collect and place in a suitable disposal container and seal securely. Containers with collected spilled material must be properly hazard labelled. Spills must be collected and disposed of according to the instructions in chapter 13.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Protective measures during use: Avoid contact with eyes and skin. Wash contaminated skin thoroughly after handling. Wear suitable protective equipment at work in case of prolonged exposure and / or high concentrations of the vapours, spray or mist.

Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Keep away from heat, sparks and open flame. Mechanical extraction is required if dust is released during handling. Open and handle containers with care. Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking.

Advices on general occupational hygiene

Do not eat, drink or smoke when using this product. Do not eat, drink, smoke or snort in the workplace. Avoid contact with skin, eyes and clothing.

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

according to Regulation (EC) No. 1907/2006 (REACH) **Revision date:** 21 Mar 2023

Print date: 21 Mar 2023 Version: 4

dentona[®]

optiprint lumina (all colors)

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Store at temperatures between 5°C and 30°C. Protect from frost and direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not smoke.

Storage class (TRGS 510, Germany): 10 – Combustible liquids that cannot be assigned to any of the above storage classes

7.3. Specific end use(s)

Recommendation:

The intended uses of this product are described in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

(country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
IDLH (US) from 1 Jan 1994	Siliciumdioxid, auf chemischem Wege gewonnen CAS No.: 112945-52-5 EC No.: 231-545-4	1 3,000 mg/m ³
OSHA (US)	Siliciumdioxid, auf chemischem Wege gewonnen CAS No.: 112945-52-5 EC No.: 231-545-4	(5) (total dust)
OSHA (US)	Siliciumdioxid, auf chemischem Wege gewonnen CAS No.: 112945-52-5 EC No.: 231-545-4	1 20 mppcf
NIOSH (US)	Siliciumdioxid, auf chemischem Wege gewonnen CAS No.: 112945-52-5 EC No.: 231-545-4	1 6 mg/m ³
IOELV (EU)	toluene CAS No.: 108-88-3 EC No.: 203-625-9	 50 ppm (192 mg/m³) 100 ppm (384 mg/m³) (may be absorbed through the skin)
IDLH (US) from 1 Jan 1994	toluene CAS No.: 108-88-3 EC No.: 203-625-9	① 500 ppm
OSHA (US)	toluene CAS No.: 108-88-3 EC No.: 203-625-9	 200 ppm 300 ppm (Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 500 ppm 10 minutes)
NIOSH (US)	toluene CAS No.: 108-88-3 EC No.: 203-625-9	 100 ppm (375 mg/m³) 150 ppm (560 mg/m³)
ACGIH (US) from 1 Jan 2021	toluene CAS No.: 108-88-3 EC No.: 203-625-9	① 20 ppm

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023 Print date: 29 Mar 2023 Version: 4



optiprint lumina (all colors)

8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	 Parameter Test material Time of sampling: Remark
ACGIH-BEI (US)	toluene CAS No.: 108-88-3 EC No.: 203-625-9	0.02 mg/L	 Toluene in blood blood Prior to last shift of workweek
ACGIH-BEI (US)	toluene CAS No.: 108-88-3 EC No.: 203-625-9	0.03 mg/L	 Toluene in urine urine end of exposure or end of shift
ACGIH-BEI (US)	toluene CAS No.: 108-88-3 EC No.: 203-625-9	0.3 mg/g creatinine	 o-Cresol in urine urine end of exposure or end of shift

8.1.3. DNEL-/PNEC-values

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure sufficient room ventilation and local exhaust ventilation. The occupational exposure limits of the product or the ingredients must be observed.

8.2.2. Personal protection equipment



Eye/face protection:

Eye protection conforming to a recognised standard should be worn if a risk assessment indicates that eye contact is possible. The following personal protective clothing should be worn: Frame goggles with side shields. DIN EN 166

Eye glasses with side protection EN 166

Skin protection:

Avoid contact with the skin. Wear suitable clothing to prevent possible skin contact. Wear protective gloves. According to the data provided by the protective glove manufacturers, it is necessary to check during their use whether the gloves retain their repellent properties and to change them as soon as damage is detected. For exposures up to 8 hours, wear protective gloves made of the following material: nitrile rubber.

Tested protective gloves must be worn EN ISO 374 Suitable material: Breakthrough time: min In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

Suitable respiratory protection must be worn if ventilation is inadequate. Wear a respirator with full face shield and the following filter cartridge: Filter against organic vapours. High efficiency particulate filters.

Filtering device with filter or ventilator filtering device of type: A

Other protection measures:

Wash contaminated skin thoroughly after handling. Wash contaminated clothing and skin immediately with plenty of water before removing clothing. Remove all contaminated clothing immediately and wash before wearing again. Do not wear contaminated work clothing outside the workplace. Do not eat, drink or smoke when using this product.

8.2.3. Environmental exposure controls

No data available

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023

Print date: 29 Mar 2023 Version: 4

dentona[®]

optiprint lumina (all colors)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Odour: ester

Colour: various

Safety relevant basis data

Parameter	Value	① Method
		② Remark
рН	not determined	
Melting point	not determined	
Freezing point	not determined	
Initial boiling point and boiling range	not determined	
Decomposition temperature	not determined	
Flash point	≥ 160 °C	
Evaporation rate	not determined	
Auto-ignition temperature	not determined	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Density	not determined	
Relative density	not determined	
Bulk density	not determined	
Water solubility	not determined	
Partition coefficient: n-octanol/water	not determined	
Dynamic viscosity	not determined	
Kinematic viscosity	not determined	

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

There is no information available Combustible

10.2. Chemical stability

Stable at normal room temperatures

10.3. Possibility of hazardous reactions

Can polymerise

10.4. Conditions to avoid

Reaction with light, risk of polymerisation. Protect from heat, flames and other ignition sources. Do not expose to high temperatures or direct sunlight. Avoid contact with Avoid contact with strong oxidising agents.

10.5. Incompatible materials

Keep away from free-radical initiators, peroxides, strongly alkaline substances and reactive metals to avoid exothermic polymerisation reactions.

10.6. Hazardous decomposition products

Carbon oxides

Gases/vapours, toxic

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023

Print date: 29 Mar 2023 Version: 4

dentona[®]

optiprint lumina (all colors)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate CAS No.: 72869-86-4 EC No.: 276-957-5

LD₅₀ oral: >5,000 mg/kg (Ratte)

LD₅₀ dermal: >2,000 mg/kg (Ratte)

Aliphatic urethane Acrylate

LD₅₀ dermal: >2,000 mg/kg (Mouse)

Triethylene glycol Dimethacrylate CAS No.: 109-16-0 EC No.: 203-652-6

LD₅₀ oral: 540 mg/kg

LD₅₀ dermal: >2,000 mg/kg (Mouse)

LC₅₀ Acute inhalation toxicity (vapour): \geq 0.139 mg/L 4 h (Rat)

LC50 Acute inhalation toxicity (dust/mist): 0.12 mg/L 4 h (Rat)

2-Propenoic acid CAS No.: 1245638-61-2 EC No.: 629-850-6

LD₅₀ oral: 540 mg/kg

LD₅₀ dermal: >2,000 mg/kg

LC₅₀ Acute inhalation toxicity (vapour): ≥0.139 mg/L 4 h (Rat)

LC₅₀ Acute inhalation toxicity (dust/mist): 0.12 mg/L 4 h (Rat)

Siliciumdioxid, auf chemischem Wege gewonnen CAS No.: 112945-52-5 EC No.: 231-545-4

LD₅₀ oral: >5,000 mg/kg (Ratte) OECD 401

LD₅₀ dermal: >5,000 mg/kg (Kaninchen)

LC₅₀ Acute inhalation toxicity (vapour): \geq 0.139 mg/L 4 h (Rat)

LC₅₀ Acute inhalation toxicity (dust/mist): 0.12 mg/L 4 h (Rat)

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS No.: 75980-60-8 EC No.: 278-355-8

LD₅₀ oral: >5,000 mg/kg (Ratte)

LD₅₀ dermal: >2,000 mg/kg (Ratte)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Harmful if inhaled.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023 Print date: 29 Mar 2023



optiprint lumina (all colors)

Additional information:

No data available

Version: 4

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,	12-diazabexadecane-1.16-divlbismethacrylate
CAS No.: 72869-86-4 EC No.: 276-957-5	
LC₅₀: 16.4 mg/L 4 d (fish)	
EC₅₀: 51.9 mg/L 3 d (fish, fish)	
EC₅₀: 51.9 mg/L 3 d (fish)	
Aliphatic urethane Acrylate	
LC ₅₀ : 16.4 mg/L 4 d (fish, Brachydanio rerio)	
EC ₅₀ : 51.9 mg/L 21 d (fish, Daphnia magna)	
Triethylene glycol Dimethacrylate CAS No.: 109-1	.6-0 EC No.: 203-652-6
LC₅₀: 16.4 mg/L 4 d (fish, Brachydanio rerio)	
EC ₅₀ : 51.9 mg/L 21 d (fish, Daphnia magna)	
EC ₅₀ : >100 mg/L 3 d (fish, Pseudokirchneriella subcar	pitata)
LC₅₀: 3.2 mg/L	
EC₅₀: 3.2 mg/L	
NOEC: 0.31 mg/L	
2-Propenoic acid CAS No.: 1245638-61-2 EC No.:	629-850-6
LC₅₀: 3.2 mg/L	
EC₅₀: 13 mg/L	
EC₅₀: 100 mg/L	
NOEC: 0.31 mg/L	
EC₅₀: 3.2 mg/L	
LC ₅₀ : ≥0.07 mg/L 21 d (crustaceans, Daphnia magna,	Danio rerio (zebrafish)) OECD 211
NOEC: ≥0.07 mg/L 21 d (crustaceans, Daphnia magn	a) OECD 211
ErC ₅₀ : 10 – 100 mg/L (Algae/water plant) OECD 201	
Siliciumdioxid, auf chemischem Wege gewonnen	CAS No.: 112945-52-5 EC No.: 231-545-4
LC₅₀: >10,000 mg/L 4 d (crustaceans, Brachydanio re	rio)
EC₅₀: >1,000 mg/L 1 d (fish, Daphnia magna)	
LC₅₀: >10,000 mg/L 4 d (Danio rerio (zebrafish))	
EC50: >10,000 mg/L 1 d (Daphnia magna (Wasserfloh	11
LC ₅₀ : ≥0.07 mg/L 21 d (crustaceans, Daphnia magna,	Danio rerio (zebrafish)) OECD 211
EC ₅₀ : >0.412 mg/L 3 d (Algae/water plant, Desmodes	mus subspicatus) OECD 201
NOEC: ≥0.07 mg/L 21 d (crustaceans, Daphnia magna	a) OECD 211
ErC ₅₀ : 10 – 100 mg/L (Algae/water plant) OECD 201	
ErC ₅₀ : 12.2 mg/L 3 d (Algae/water plant, Desmodesm	us subspicatus)
liphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	CAS No.: 75980-60-8 EC No.: 278-355-8
LC ₅₀ : =6.53 mg/L 2 d (fish, Oryzias latipes)	
EC ₅₀ : >2.01 mg/L 3 d (Algae/water plant, Pseudokirch	neriella subcapitata, Oryzias latipes (Mikroorganismen))
EC ₅₀ : >1,000 mg/L (Activated sludge)	
	igna)

Aquatic toxicity:

Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023

Print date: 29 Mar 2023 Version: 4



optiprint lumina (all colors)

12.2. Persistence and degradability

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate CAS No.: 72869-86-4 EC No.: 276-957-5

Biodegradation: Poorly biodegradable.

Aliphatic urethane Acrylate

Biodegradation: Yes, slowly

Triethylene glycol Dimethacrylate CAS No.: 109-16-0 EC No.: 203-652-6

Biodegradation: Yes, slowly

2-Propenoic acid CAS No.: 1245638-61-2 EC No.: 629-850-6

Biodegradation: Yes, slowly

12.3. Bioaccumulative potential

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate CAS No.: 72869-86-4 EC No.: 276-957-5

Log K_{OW}: 3.39

Triethylene glycol Dimethacrylate CAS No.: 109-16-0 EC No.: 203-652-6

Log K_{OW}: 1.69

2-Propenoic acid CAS No.: 1245638-61-2 EC No.: 629-850-6

Log K_{OW}: 1.69

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate CAS No.: 72869-86-4 EC No.: 276-957-5

Results of PBT and vPvB assessment: -

Christobiltmehl CAS No.: 14464-46-1 EC No.: 238-455-4

Results of PBT and vPvB assessment: –

Aliphatic urethane Acrylate

Results of PBT and vPvB assessment: —

Triethylene glycol Dimethacrylate CAS No.: 109-16-0 EC No.: 203-652-6

Results of PBT and vPvB assessment: -

2-Propenoic acid CAS No.: 1245638-61-2 EC No.: 629-850-6

Results of PBT and vPvB assessment: —

Siliciumdioxid, auf chemischem Wege gewonnen CAS No.: 112945-52-5 EC No.: 231-545-4

Results of PBT and vPvB assessment: -

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS No.: 75980-60-8 EC No.: 278-355-8

Results of PBT and vPvB assessment: -

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Contact the responsible, authorised waste disposal company about waste disposal.

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023

Print date: 29 Mar 2023 Version: 4



optiprint lumina (all colors)

Other disposal recommendations:

Avoid release to the environment.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number		
UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper ship	ping name		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport haza	rd class(es)		
9	9	9	9
14.4. Packing group			<u>.</u>
111	111	111	111
14.5. Environmental	hazards		
		MARINE POLLUTANT	
14.6. Special precau	tions for user		
Special Provisions: 274 335 375 601 Limited quantity (LQ): 5 L	Special Provisions: 274 335 375 601 Limited quantity (LQ): 5 L	Special Provisions: 274 335 969 Limited quantity (LQ): 5 L	Special Provisions: A97 A158 A197 A215 Limited quantity (LQ): Y964
Excepted Quantities (EQ): E1	Excepted Quantities (EQ): E1	Excepted Quantities (EQ): E1	Excepted Quantities (EQ): E1
Hazard identification number (Kemler No.): 90	Classification code: M6	EmS-No.: F-A, S-F	
Classification code: M6			
Tunnel restriction code: (-)			

14.7. Maritime transport in bulk according to IMO instruments No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

EU regulations

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has been carried out for this preparation. Chemical safety assessments for substances in this mixture have not been carried out

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023 Print date: 29 Mar 2023

Version: 4

dentona[®]

optiprint lumina (all colors)

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

- ACGIH American Conference of Governmental Industrial Hygienists
- ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging
- DIN German Institute for Standardization / German Industrial Standard
- DNEL derived no-effect level
- EC_{50} Effective Concentration 50%
- EN European Standard
- ES Exposure scenario
- ICAO International Civil Aviation Organization
- IMDG International Maritime Dangerous Goods
- IMO International Maritime Organization
- LC₅₀ Lethal (fatal) Concentration 50%
- LD₅₀ Lethal (fatal) Dose 50%
- MAK Maximum concentration in the workplace air (CH)
- NFPA National Fire Protection Association
- NIOSH National Institute for Occupational Safety & Health
- NOEC No Observed Effect Concentration
- OECD Organisation for Economic Cooperation and Development
- OEL Threshold Limit Value
- OSHA Occupational Safety & Health Administration
- PBT persistent and bioaccumulative and toxic
- PNEC Predicted No Effect Concentration
- REACH Registration, Evaluation and Authorization of Chemicals
- RID Dangerous goods regulations for transport by rail
- TRGS Technische Regeln für Gefahrstoffe
- UN United Nations
- ZNS central nervous system

16.3. Key literature references and sources for data

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008

on classification, labelling and packaging of substances and mixtures, amending and repealing of Directives 67/548/EEC and 1999/45/EC and amending Regulation (EC) No 1907/2006.

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	Calculation method.
Serious eye damage/eye irritation (Eye Dam. 1)	H318: Causes serious eye damage.	Calculation method.
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	Calculation method.
Hazardous to the aquatic environment (Aquatic Acute 1)	H400: Very toxic to aquatic life.	Calculation method.
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	Calculation method.

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 21 Mar 2023

Print date: 29 Mar 2023 Version: 4

dentona[®]

optiprint lumina (all colors)

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements		
H225	Highly flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H336	May cause drowsiness or dizziness.	
H361d	Suspected of damaging the unborn child.	
H361f	Suspected of damaging fertility.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

16.6. Training advice

As from 24 August 2023 adequate training is required before industrial or professional use.

16.7. Additional information

This information is based on our current knowledge and is intended to describe the product in terms of health, safety and environmental conditions only. It should therefore not be construed as a guarantee of any specific property of the product.

DISCLAIMER We have obtained the information contained in this data sheet from sources we believe to be reliable. The accuracy of the information, whether expressed or implied, cannot be guaranteed. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and possibly beyond our knowledge. For these and other reasons, we assume no responsibility and expressly disclaim liability for any loss, damage or expense which may arise from or be in any way connected with the handling, storage, use or disposal of the product. This safety data sheet has been prepared for this product and may only be used for this product. If the product is used as a component of another product, the information given in the data sheet may not apply.End of safety data sheet

End of safety data sheet

* Data changed compared with the previous version.